

Ruggedized/Industrial/Outdoor Display

Ruggedized Display RD55 (55")*

- Comprehensive military-grade protection with MIL-STD-810, 461, 901D, and 1275
- 1920 x 1200 resolution for crisp and clear visual display
- Versatile I/O options with VGA, DVI, HDMI, and DP ports
- Optional military circular connectors



Industrial Display ID43 (43") / ID55 (55")

- Ultra HD quality with 3840 x 2160 resolution for unmatched clarity and sharpness
- 700 nits brightness and 3000:1 contrast ratio for visibility in diverse lighting conditions
- Versatile I/O options with RS232, HDMI, DP, and VGA ports
- Compatible with optional wall mount or stand for flexible configuration






Outdoor Display OD32 (32") / OD43 (43") / OD55 (55") / OD65 (65")

- Full HD quality with 1920 x 1080 resolution for crisp and clear visual display
- 2,500 nits brightness and 3000:1 contrast ratio for visibility in high ambient lighting conditions and under direct sunlight
- IP54 rating for water-resistance as well as protection from dirt and dust
- Versatile I/O options with RS232, HDMI, DP, DVI, and VGA ports



*Also available in customized screen sizes ranging from 7" to 65"

Specifications

	Ruggedized Display	Industrial Display	Outdoor Display
Display			
Resolution	1920 x 1200	3840 x 2160 (UHD)	1920 x 1080 (FHD)
Brightness	250 to 1,000 nits	700 nits	2,500 nits
Contrast Ratio		3000:1	3000:1
I/O Interface	Standard I/O connectors VGA *1 HDMI *1 DVI *1 DP *1 Optional military circular connectors	RS232 *1 DP *2 Speaker *2 VGA *1 HDMI *2	RS232 *1 DP *1 Speaker *2 DVI *1 HDMI *2 VGA *1
Power	AC adapter (90-264VAC)	AC adapter (100-240VAC, 50/60Hz)	AC adapter (100-240VAC, 50/60Hz)
Dimensions (W x H x D) & Weight		ID43 43" Display: Dimensions: 1010 x 617 x 86mm (39.8" x 24.3" x 3.4") Weight: 29kg (63.9lbs) ID55 55" Display: Dimensions: 1239 x 709 x 73mm (48.8" x 27.9" x 2.9") Weight: 42kg (92.6lbs)	OD32 32" Display: Dimensions: 758 x 467 x 84mm (29.8" x 18.4" x 3.3") Weight: 21kg (46.3lbs) OD43 43" Display: Dimensions: 1000 x 588 x 107mm (39.4" x 23.1" x 4.2") Weight: 29kg (63.9lbs) OD55 55" Display: Dimensions: 1272 x 742 x 111mm (50.1" x 29.2" x 4.4") Weight: 48kg (105.8lbs) OD65 65" Display: Dimensions: 1500 x 876 x 123mm (59.1" x 34.5" x 4.8") Weight: 74kg (163.1lbs)
Environmental Specifications	Temperature: - Operating: -10°C to 55°C (14°F to 131°F) - Storage: -20°C to 70°C (-4°F to 158°F) Humidity: - 5-95% RH at 30°C, non-condensing	Temperature: - Operating: 5°C to 35°C (41°F to 95°F) - Storage: -20°C to 55°C (-4°F to 131°F) Humidity: - 20-80% RH, non-condensing	
Waterproof			IP54
Accessories		HDMI cable 1.8m (5.9ft) Power cord 1.8m (5.9ft) Remote controller Optional: Wall mount / Stand	HDMI cable 1.8m (5.9ft) Power cord 1.8m (5.9ft) Remote controller Protective glass
Ruggedized Features	MIL-STD-810 certified MIL-STD-461 certified MIL-STD-901D certified MIL-STD-1275 certified		

Connect with Us



Email



LinkedIn



Website